

# Photon Pair Generation at 780 and 1560 nm in Periodically Poled Silica Fiber


Jeffrey Ming Han Li<sup>1</sup>, Alexander C.B. Greenwood<sup>1</sup>, Adi Shahaj<sup>1</sup>, Changjia Chen<sup>1</sup>, Brian T. Kirby<sup>2,3</sup>, Alexei V. Gladyshev<sup>4</sup>, Peter G. Kazansky<sup>5</sup>, Li Qian<sup>1</sup>

- <sup>1</sup>Dept. of Electrical & Computer Engineering, University of Toronto, 10 King's College Rd., Toronto, Ontario, Canada M5S 3G4,
- <sup>2</sup>Tulane University, New Orleans, Louisiana 70118, USA, <sup>3</sup>DEVCOM Army Research Laboratory, Adelphi, Maryland 20783, USA,
- <sup>4</sup>Prokhorov General Physics Institute of the Russian Academy of Sciences, Dianov Fiber Optics Research Center, Moscow, Russia
- <sup>5</sup>Optoelectronics Research Centre, University of Southampton, Southampton SO17 1BJ, United Kingdom

#### Motivation


#### **Quantum Repeater Protocols**

- Distant Quantum Memory Device (QM) can be entangled via interaction with entangled Photon Source performing a Bell-State Measurement (BSM) at an intermediate node [1].



#### **Ground-Satellite Communications**

- Non-degenerate sources can establish correlations between satellites and ground-based trusted nodes.[2].



### **Heralded Single Photon Sources**

- Single photons in the C-band can be heralded by detecting 780nm light.



## Periodically-Poled Silica Fiber

-An effective  $\chi^{(2)}$  is introduced to a step-indexed, Ge-doped fiber via thermal poling.





Figure 1:(a) The cross-section of a twin-hole fiber (THF). (b) Two electrodes through the twin hole introduce polarization (c) The polarization can be periodically erased with UV tight for Quasi-phase matching condition(QPM).

The effective nonlinearity will depend on the "frozen-in" DC field  $E_{DC}$ :  $\chi^{(2)} = 3\chi^{(3)}E_{DC}$ .



### **Entangled Photon Pair in Fiber**


Collinear pairs of photons can be generated in PPSF via spontaneous parametric downconversion.



The state of the biphoton pairs exiting a type-II SPDC source can be decomposed into its spectral components as

$$|\psi\rangle = \int d\omega_s \int d\omega_i \left( f_-(\omega_s, \omega_i) | H, \omega_s \rangle | V, \omega_i \rangle + f_+(\omega_s, \omega_i) | H, \omega_i \rangle | V, \omega_s \rangle \right),$$

where  $f_{+/-}(\omega_s,\omega_i)$  are spectral amplitudes determined by the dispersive properties of the medium and the quasi-phase matching conditions [4].



# Non-Degenerate Source

- A QPM period of  $\Lambda=38.16~\mu m$  will yield photon pairs at 780 and 1560 nm when pumped with 520 nm light.





Figure 2: (a) A simulated tuning curve of signal and idler photons emitted from a Type-0 SPDC process near the degeneracy wavelength at  $\sim$  1066 nm. (b) and (c) The spectral brightness of signal and idler photons for a pump near 520 nm. The single photon bandwidth is reported to be 1 nm  $\approx$  489 GHz (FWHM) when centered at 780 nm.

# Gating Function & Coincidence

-The generated photon pairs are detected by concentrating the detection windows of the detectors near the SPDC signals using the Gating Function



-The ID220 detects 1560nm idler photon to gate the SPCM for 780 nm signal photon detection.




Figure 3: Demonstration of the SPCM detector being gated by the ID220 to concentrate the detection window to the vicinity of the SPDC signals.




Figure 4: Experimental plot of the peak photon count on the coincidence histogram, obtained by sweeping the wavelengths of the tunable filters to locate the SPDC signals. A peak at 780nm and 1560nm are observed for a 520.002 nm pump laser, matching the simulation

- [1] C. Simon, H. de Riedmatten, M. Afzelius, N. Sangouard, H. Zbinden, and N. Gisin, "Quantum repeaters with photon pair sources and multimode memories," *Physical Review Letters*, vol. 98, no. 19, 2007.
- [2] M. Aspelmeyer, T. Jennewein, M. Pfennigbauer, W. R. Leeb, and A. Zeilinger, "Long-distance quantum communication with entangled photons using satellites," *IEEE Journal of Selected Topics in Quantum Electronics*, vol. 9, no. 6, pp. 1541–1551, 2003.
- [3] Y. S. Lee, M. Xie, R. Tannous, and T. Jennewein, "Sagnac-type entangled photon source using only conventional polarization optics," *Quantum Science and Technology*, vol. 6, no. 2, p. 025004, 2021.

[4] C. Chen, E. Y. Zhu, A. Riazi, A. V. Gladyshev, C. Corbari, M. Ibsen, P. G. Kazansky, and L. Qian, "Compensation-free broadband entangled photon pair sources," *Optics Express*, vol. 25, no. 19, p. 22667, 2017.

#### **Acknowledgements**





